

OIL SPECIFICATIONS

EPA 17, EPA 21, AND EPA 24 MX ENGINES

	5W40	10W40	15W40	5W30	10W30
MX-11	CK-4	CJ-4, CK-4	CK-4	CK-4	CK-4
MX-13	CK-4	CJ-4, CK-4	CK-4	CK-4	CK-4

If using the CJ-4 oil in EPA 2017, the EPA 2013 service intervals must be used.

RECOMMENDED APPROVED

MAINTENANCE INTERVALS

MAINTENANCE ITEM		MI.	KM.
OIL AND FILTER	Severe/vocational duty Normal/line haul > 20% idle time Normal/line haul < 20% idle time	30,000 50,000 75,000	48,000 80,000 120,000
FUEL FILTER*	Severe/vocational duty Normal/line haul > 20% idle time Normal/line haul < 20% idle time	30,000 50,000 75,000	48,000 80,000 120,000
COOLANT FILTER		300,000	480,000
DEF FILTER		300,000	480,000
DPF DRY CLEANING	Severe/vocational duty Normal/line haul	150,000 300,000	240,000 480,000
DPF WET CLEANING	Normal/line haul	600,000	965,000

*Use of poor quality fuel may require more frequent fuel filter service.

For complete maintenance schedules, please see the MX Engine Operator's Manual.



PACCAR Inc. - P.O. Box 1518, Bellevue, WA 98009 PACCAR MXmaint/24



Note: This document is to be considered a summary of oil specs and service intervals and to be used for reference only. For full maintenance details, the PACCAR MX Operator's Manual should be referenced. Consult with your PACCAR Powertrain distributor at time of ordering for standard and optional equipment. PACCAR MX-11, MX-13 are trademarks of PACCAR Inc. Visit www.paccarpowertrain.com to find your local dealer. ©2024 PACCAR Inc.