



PEAK HORSEPOWER	PEAK TORQUE (LBFT. @ RPM)
200	600 @ 1,300)
220	600 @ 1,300	
240	600 @ 1,300	,
250	660 @ 1,400	
260¹	660 @ 1,400	,
2801	660 @ 1,400	
300¹	660 @ 1,600	1
325 ¹	750 @ 1,600	,
340 ²	700 @ 1,500	1
360 ²	800 @ 1,800)

¹Also Fire Service Rating ²Fire Service Rating Only







CONFIGURATION **BORE X STROKE (MM) DISPLACEMENT DRY WEIGHT OIL SYSTEM CAPACITY**

HORSEPOWER PEAK TORQUE

Inline 6-cylinder

107x124 6.7 L.

1,150 LBS.

19.5 U.S. QTS.

200-360 HP

520-800 LB.-FT.

GOVERNED SPEED

CLUTCH ENGAGEMENT TORQUE³

BASE WARRANTY⁴

CERTIFICATION

2,600 RPM

400 LB.-FT. @ 700 RPM

3 YRS./UNLIMITED MILES

EPA 2024

³Determined By Engine Horsepower and Idle Setting ⁴Extended Protection Plans Available

MAINTENANCE INTERVALS

SPECIFICATIONS

MAINTENANCE ITEM	MI.	KM.
Fuel Filter	60,000 ⁵	96,000
Oil and Filter	30,000 ⁵	48,000
DEF Filter	200,000	320,000

⁵Duty cycle dependent. Please reference Operator's Manual.

