



PACCAR TX-12 PRO

**DRIVE
EFFICIENTLY.
WORK
CONFIDENTLY.**

PACCAR's TX-12 Pro delivers an impressive combination of performance and efficiency. The purpose-built automated transmission is perfect for vocational applications that don't require the high engine torque and GCWR covered by the PACCAR TX-18 series.

PACCAR TX-12 PRO HIGHLIGHTS



Wide ratio coverage for excellent low-speed maneuverability

Extreme Duty Clutch for increased durability and extended maneuvering time in adverse soil conditions

Secondary Configuration allows driver to toggle between two calibrations to tailor for load or terrain

Vocational specific features including off-highway calibration, rock-free mode, and paver assist

Standard 8-bolt bottom and 4-bolt rear PTO mounting locations with combined 95 horsepower capacity

Transmission fluid temperature and pressure sensors alert driver of potential issues before system damage occurs

Cooler-less design eliminates the risk of cooler leaks and costly repairs

KEY SPECIFICATIONS & CAPACITIES

GEARS	12 Forward / 2 Reverse
TORQUE CAPACITY	1,700 LB.-FT.
OIL CAPACITY	16 PTS.
SYSTEM WEIGHT	665 LBS.
MAXIMUM OPERATING WEIGHT	70,000 LBS.
PTO MAXIMUM CAPACITY	8-bolt, Bottom Mount, 4-bolt Rear, 95HP
OIL TEMPERATURE AND PRESSURE SENSOR	Yes

WARRANTY COVERAGE

TRANSMISSION	3 YRS./300K MI./480K KM.
CLUTCH	3 YRS./300K MI./480K KM.

MAINTENANCE INTERVALS

TRANSMISSION	250K MI. (400K KM.) Oil Change
CLUTCH	Maintenance Free

RATIOS

1ST	14.43
2ND	11.05
3RD	8.44
4TH	6.46
5TH	4.95
6TH	3.79
7TH	2.91
8TH	2.23
9TH	1.70
10TH	1.30
11TH	1.00
12TH	0.77
REVERSE 1	16.92
REVERSE 2	12.95
OVERALL	18.85